# **VERTEX ELECTRIC RADIATORS**



# Heat any room quickly and easily with Vertex electric radiators!

# Main advantages

- Simple and intuitive operation
- Operated by supplied RF thermostat
- Boost function
- Open window detection
- ECO Design compliant
- Ready for installation and connection
- Easy pairing with RF Thermostat







#### Electric vertical radiator Vertex E or the decorative version Vertex Plan E

The Vertex E is the electric version of our vertical radiator. It saves space due to its vertical design, and only needs a socket to quickly achieve a high heat output.

The Vertex Plan E combines the advantages of a vertical electric radiator with a sleek and decorative appearance. With its flat front, it stands out in the most beautiful interiors, even in small rooms, which saves space.

#### **Product range**

	Electric power (Watt)	Length	Height	Height Incl. receiver	Article number
VERTEX E	1250	500	1800	1867	0274A181105
VERTEX E	1500	600	1800	1867	0274A181106
VERTEX E	1750	700	1800	1867	0274A181107
VERTEX PLAN E	1250	500	1800	1867	0275A181105
VERTEX PLAN E	1500	600	1800	1867	0275A181106
VERTEX PLAN E	1750	700	1800	1867	0275A181107

## **Intelligent RF thermostat**

Temperature setting	Adjustable from $+$ 10 °C to $+$ 30 °C.
4 possible operating modes	Auto (programming), Comfort, Eco, Frost protection.
General use	7-day program: Up to six different profiles can be assigned to each day. Super Comfort Function: The temperature is increased by 2 ° C, adjustable from 20 to 120 minutes.  Boost: The output is temporarily increased to the maximum, adjustable from 10 to 60 minutes. Weekly programmable.
Open window detection	Automatic switch to frost protection mode when a significant temperature drop is detected.
Child safety	The control panel can be locked.
Control	Connection to the radiator is quick and easy. Can control multiple radiators. Ergonomic: backlit display, adjustment is simple and intuitive.

### **Technical specifications**

Color	The standard color is Stelrad white 9016, 35 different Stelrad colors and more than 200 RAL colors are available at an additional cost (see Website / Catalog).
Radiator	The electric radiator is pre-filled with heating liquid. Equipped with an RF receiver with 0,8 m insulated cable with plug. The radiator comes with an RF thermostat and consoles.
Mains voltage	230VAC-50Hz
Warranty	10 years on the radiator and 2 years on electrical parts, if the installation conditions are respected and the Stelrad warranty regulations are met.
Standards Radiator	CE, IP44, class II.



www.stelrad.eu